EPSON[®]

PowerLite[®] 815E

3LCD Extreme Short Throw Lamp-Free Laser Display with 4K Enhancement¹



Take classroom and meeting room displays beyond the limits of flat panels.



Stunning color and impactful image quality with 3-chip 3LCD technology — virtually glare-free from anywhere in the room, unlike flat panels; 5,000 lumens of color and white brightness²

Astonishingly smooth display with 4K Enhanced resolution¹ — Epson's advanced pixel-shifting technology combined with innovative frame interpolation, HDR and scene adaptive gamma image processing provides visibly smooth and more detailed picture quality

Large, up to 160" diagonal image — 80" image from just 1" away from the wall or 100" from 4" away; at under 28 pounds, this lightweight projector can deliver an image up to 160" diagonal; 4.5 times larger than a 75" flat panel

Built-in flexible digital canvas for easy integration – 16:9 native aspect ratio with additional support for ultra wide 16:6 and 21:9 for equitable conferencing experience in meeting rooms

Lamp-free technology — a virtually maintenance-free laser light source of up to 30,000 hours³ combined with a sophisticated re-engineered cooling system eliminates the need to ever purchase or replace a lamp again

Fully loaded to support your latest needs — multiple HDMI[®] ports, built-in wired/wireless networking, HDBaseT[®], RS-232c connectivity and Miracast[®]; dynamic dual speaker sound system to fill virtually any room

Streamlined setup — digital zoom and image shifting make image alignment easy for desktop or wall-mounted display; Epson Setting Assistant app⁴ ensures easy installation by automatically smoothing edges and corners

Complex tasks made easy — with timesaving tools such as Wake On signal; multiple EDID settings with digital image correction for ease of installation for nearly any image size/aspect ratio; built-in media player supports Epson[®] content management software

FPSON

Specifications

Projection System RGB liquid crystal shutter projection system

Driving Method Poly-silicon TFT active matrix Native Resolution 1080p with 4K Enhancement¹ (1920 x 1080 x 2)

Resolution on Screen 1080p with 4K Enhancement¹ (4.1 million pixels)

Pixel Number: 2,073,600 pixels (1920 x 1080) x 3 chips Color Brightness² Color light output: 5,000 lumens White Brightness² White light output: 5,000 lumens Aspect Ratio Supports 16:9, 16:10, 4:3, 21:9*, 16:6* (with vertical image shift control within letterbox area) * 21:9 and 16:6 images can be adjusted vertically within the letterbox area. When using digital zoom, images can be adjusted vertically and horizontally within the letterbox area. Throw Ratio Range 0.16 (Zoom: Wide), 0.22 (Zoom: Tele)

Image Size (Projected Distance)

80" to 160" (Zoom Wide: 10.9" – 22.7") at 16:9 74" to 148" (Zoom Wide: 10.9" – 22.7") at 16:10 66" to 130" (Zoom Wide: 10.9" – 22.7") at 4:3 76" to 151" (Zoom Wide: 10.9" – 22.7") at 21:9 75" to 148" (Zoom Wide: 10.9" - 22.7") at 16:6

Light Source Laser diode Light Source Life³

Normal Mode: Up to 20,000 hours Extended Mode: Up to 30,000 hours Dynamic Contrast Ratio Over 2,500,000:1 Color Reproduction Up to 1.07 billion colors Manual Keystone Correction/Foot Adjuster

Vertical: ±3.6 degrees

Horizontal: ±0.9 degrees **Display Modes** Dynamic Presentation Cinema Natural BlackBoard DICOM SIM

Multi-Projection Face Brightness

Projection Lens

Type Digital zoom, Focus (manual) F-Number 1.8 Focal Length 2.3 mm Zoom Ratio 1 – 1.35 (digital zoom)

Software

Epson Setting Assistant app (Google Play[™] Store/Apple[®] App Store®)

Epson iProjection^{™5}

Epson Projector Management (desktop/connected) In addition to compatibility with Epson's standard suite of software, this product has a direct playback function via USB. Works with:

- Epson Projector Content Management (visit our support pages for the latest version)
- Epson Creative Projection app for iOS®

Interfaces

2x HDMI (HDCP 2.3)

- 1x HDBaseT
- 1x HDMI (out)
- 1x RS-232c Control Port
- 1x USB Connector Type A (data/wireless)
- 1x USB Connector Type A (power 5 A, 2 V and data)
- 1x USB Connector Type B (firmware update)

1x Wired LAN RJ-45

Built-In Wireless Support: Infrastructure, Firmware Update, USB Display and Access Point - Wi-Fi Direct® IEEE 802.11b (2.4 GHz): 11 Mbps* (infrastructure only) IEEE 802.11g (2.4 GHz): 54 Mbps* IEEE 802.11n (2.4 GHz): 72.2 Mbps* IEEE 802.11a (5 GHz): 54 Mbps* IEEE 802.11n (5 GHz): 150.0 Mbps*

IEEE 802.11ac (5 GHz): 325 Mbps*

Wi-Fi CERTIFIED[™] Miracast R2 * Maximum speed and range are achievable when used with same enhanced mode technology. Actual features

and performance may vary depending on your computer system, the environment and other factors.

Compatible Network Control/Management

Microsoft Teams® Front Row. PJ-Link Class-2. Art-Net. Crestron® Connected, Extron[®] IP Link, Extron XTP, AMX[®] Device Discovery

Other

Speakers 2x 8 W **Operating Temperature** 32 °F to 104 °F (0 °C to 40 °C) Storage Temperature: 14 °F to 140 °F (-10 °C to 60 °C) (20% – 80% humidity, no condensation) Power Supply Voltage 100 V - 240 V AC \pm 10%, 50 Hz/60 Hz Auto Power On Signal Detection on HDMI/Plug-In Detection

Power Consumption Normal Mode: 398 W Quiet Mode: 296 W Standby Mode: 2.0 W Energy-Saving Mode: 0.4 W Fan Noise Normal Mode: 35 dB Quiet Mode: 26 dB

Security Enterprise-level security encryption Country of Origin: Philippines

Dimensions (W x D x H)

Projector 27.4" x 13.5" x 5.7 Weight 27.6 lb

Remote Control

Features

Power, A/V Mute, Split, E-Zoom, Volume, HDMI, LAN, ESC, Num, Auto, Enter, Directional Arrows, Menu, Effect, Source Search, USB, Computer, Color Mode, Default, ID, Aspect, Freeze, User, Home **Operating Angle**

Front: Right/Left: -30 to +30 degrees, Upper/Lower: 0 to +60 degrees Rear: Right/Left: -55 to +55 degrees, Upper/Lower: +75 to +15 degrees Operating Distance 20 ft (6 m)

Security

Infrastructure: OPFN WPA2/WPA3-PSK WPA2/WPA3-EAP Supported EAP: PEAP, PEAP-TLS, EAP-TLS, EAP-Fast Access Point (Wi-Fi Direct): WPA2-PSK(AES)

Eco Features

RoHS compliant End-of-life options available Epson America, Inc. is a SmartWay® Transport Partner7

Limited Warranty and Service

Warranty Three-year limited in the U.S. and Canada **Service** Whole unit exchange, usually Next-Business-Day⁸, Toll-free telephone support, Monday through Friday Epson ConnectionSM

Pre-Sales Support (U.S. and Canada): 800-463-7766 Website: www.epson.com

Epson Preferred[™] Plus Extended Service Plan[®]

1-Year Next-Business-Day Whole Unit Exchange EPPEXPE1 2-Year Next-Business-Day Whole Unit Exchange9 EPPEXPF2 (available for up to a total of 5 years of continuous coverage)

What's Included

Contact:

PowerLite 815E, Quick Setup Guide, Projector Remote Control, 2x AA Batteries, 6' Power Cord

Ordering Information

PowerLite 815E	V11HA99120
Extreme Short Throw Wall Mount (White) (ELPMB75)	V12HB12010
Wireless LAN Adapter (ELPAP11)	V12H005A02
Replacement Air Filter (ELPAF64)	V13H134AE0
DC-07 Document Camera	V12H759020
DC-13 Document Camera	V12H757020
DC-21 Document Camera	V12H758020
DC-30 Document Camera	V12HB09020
100" Ambient Light Rejecting Screen (16:9)*	V12H002AL0
120" Ambient Light Rejecting Screen (16:9)*	V12H002AM0
* For use with tabletop projector installation only	

For use with tabletop projector insta

1 4K Enhancement Technology shifts each pixel to surpass Full HD resolution on screen. 12 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. 1 3 No required maintenance for the light source for up to 30,000 hours (Extended Mode) or 20,000 hours (Normal Mode). Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. 14 Internet connection required for download. Data usage fee may apply. 15 For wireless functionality, including via the Epson iProjector functs be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson IProjection Agence yot that reduces greenhouse gases and other air pollutants and improves fuel efficiency. 18 Product comes with a 3-year limited warranty with the option to purchase Extended Service Plans up to a total of 5 years of continuous coverage. Extended Service Plan can be purchased at any time that you are covered under an Epson limited warranty or Epson Extended Service Plan. See individual service plan for details. 9 Expedited shipping not available in all areas. Orders must be placed and processed by 1 p.m. Pacific Time, Monday through Friday, excluding holidays.

Learn more about how our products can empower your institution. Visit us at www.epson.com/foreducation



Epson America, Inc. 3131 Katella Ave., Los Alamitos, CA 90720

Epson Canada Limited 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON and PowerLite are registered trademarks and Epson iProjection is a trademark of Seiko Epson Corporation. Epson Connection and Epson Preferred are service marks of Epson America, Inc. Apple and App Store are trademarks of Apple Inc., registered in the U.S. and other countries. Microsoft Teams is a trademark of the Microsoft group of companies. Google Play is a trademark of Google LLC. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. Miracast® and Wi-Fi Direct® are registered trademarks and Wi-Fi CERTIFIEDTM is a trademark of Wi-Fi Alliance[®]. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2023 Epson America, Inc. CPD-63700R1 10/23